



Eva - Emp 3.0



TTT-TwinTasteTech

Rubino 200 TTT

Description

Rubino 200 TTT is a completely automatic table-top vending machine of the last generation with design and technical performance at the top of the range. It is equipped with the new Saeco TTT-TwinTasteTech brewing unit that allows the dispensing of both paperless fresh brew coffee and espresso coffee without any software or mechanical presetting. The product can be selected by simply pressing a button on the direct access keypad.

Designed for small and medium locations, it is available with cabinet in two versions, standard and for payment system, and dispenses up to 8 different beverages.

Accessories

- Cabinet with height-adjustable feet (w x h x d 410 x 810 x 550 mm, 23 kg)
- Cabinet with height-adjustable feet suitable for change giver (w x h x d 410 x 810 x 550 mm, 24 kg)
- Independent water tank kit
- Timekeeper kit
- Validator kit
- 5-button keypad kit
- Memory key to copy and quickly transfer machine settings
- Eva-Dts kit

Main features

- Machine in energy class A (EVA - EMP 3.0)
- Automatically dispenses cups (up to 195), sugar and stirrers
- Paperless fresh brew and/or espresso coffee dispensing from ground coffee or coffee beans thanks to Saeco TTT-TwinTasteTech brewing unit
- Accepts the most commonly used parallel and serial MDB, BDV and Executive (possible Master and Slave configurations) payment systems
- 6 gr to 10 gr adjustable doser
- Possibility to dispense products up to 10 ounces
- Customisable settings

User interface

- Direct access 8-button keypad for beverage selection
- 2 keys for sugar preselection
- Option to set 2 preselection keys: one for decaffeinated/barley and one for no-cup option
- 2-line, 20-character alphanumeric display
- Both fresh brew and espresso coffee can be selected using the direct access keypad

Technical data

Rubino 200 TTT

Structural specifications

Dimensions (w x h x d)	410 x 765 x 535 mm
Weight	46 kg

Electrical specifications

Power supply	230V/50 Hz - 120V/60 Hz
Power consumption	1250 W

Water specifications

Boiler material	brass
-----------------	-------

Water connections

Water connection	3/4" (1 – 8 bar)
Water supply	standard: water supply - optional: independent water tank kit
Independent water tank	20 l

Other specifications

Cups (h 70 mm)	195
Cups type ø	70 or 73 mm
Stirrers	180
Available stirrers	90 - 105 - 115 mm
Coffee bean container	1
Ground coffee container	1
Instant product container	2
Sugar container	1
Number of selections	8
Number of preselections	up to 4
Disc mixer	2
Brewing unit	10 gr

Canisters capacity

Coffee beans	2.0 kg
Ground coffee	1.0 kg
Instant coffee	0.7 kg
Milk	0.85 kg
Chocolate	1.7 kg
Sugar	2.0 kg

Technical specifications

- Pre-galvanized and painted steel-sheet body
- Thermoplastic door
- Thermoplastic cover with transparent coffee bean container
- Containers and tanks in food-contact approved polypropylene
- Water, coffee and cup-empty signal
- Hot water solenoid valve
- Software function setting the maximum number of coffee cycles permitted before the dump box is removed and emptied
- Electronically controlled boiler temperature
- Electromechanical pulse counter
- Exhauster to absorb internal moisture and additional steam exhauster for the dispensing area
- Removable cup-releasing device for easy cleaning and checking
- 60 W electromagnetic vibration pump
- Anti-overflow air-break device
- Simplified error reset
- Boiler safety valve
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- Energy class A (EVA - EMP 3.0)
- CE, VDE and CSA approved

